

### UPS 18kVA rental facility

Input:	AC: HAN 6-pole with adapter to 32A-CEE DC: HAN 16-pol.
Output:	AC: HAN 6-pole with adapter to 32A-CEE
Details:	Protection: IP20, IP44 with rain cover Dimensions: H x W x D in mm: 740 x 700 x 1,000 H x W x D in mm: 975 x 840 x 1,240 in transport rack The battery pack is available in a separate case H x W x D in mm: 620 x 700 x 1,000 H x W x D in mm: 905 x 840 x 1,240 in transport rack
Weight:	135kg (UPS-Module) / 240kg in transport rack +311kg (18Ah Battery) / +416kg in transport rack +194kg (9Ah Battery) / +299kg in transport rack
Runtime for an assumed cos-phi of 0.8:	from 10min (with 18Ah battery) from 3.5min (with 9Ah battery) Runtime for an assumed cos-phi of 0.8: from 10min (with 18Ah battery) from 3.5min (with 9Ah battery) High runtimes possible when units combined
Extras:	Reliable, uninterrupted supply of your technology 5 operating modes to choose from Alarm function configurable at low battery level Automatic power reset Network card NetMan
Transport:	Optional transport frame available (stackable). The UPS as well as the battery units can be operated.



Front side



Rear side



battery case in the  
transport rack



UPS in the  
transport rack