

Power units from 15 to 400 kVA, with cowlings



Output in kVA	Output in kVA	approx. length in mm	approx. with in mm	approx. height in mm	approx. weight in kg	approx. tank volume in litres	Connection system	dB(A)at 7m
15	12	1.770	930	1.720	1.195	132	1 x wall socket CEE 63 A	57
15	12	2.170	1.030	2.200	2.190	800	1 x wall sockete CEE 63 A	58
35	28	2.210	1.160	1.860	1.920	267	1 x wall socket CEE 63 A	62 (55)*
50	40	2.290	1.095	1.905	2.000	270	1 x wall socket CEE 125 A	68 (56)*
60	48	2.300	1.200	1.855	2.150	295	1 x wall socket CEE 125 A	63
70	56	2.300	1.200	2.075	2.180	276	1 x wall socket CEE 125 A	70
100	80	2.980	1.250	2.260	3.100	450	Connection tracks	68
125	100	3.330	1.290	2.190	3.490	540	Connection tracks	64
150	120	3.760	1.400	2.500	4.440	650	Connection tracks	65
175	140	3.360	1.250	2.450	3.880	483	Connection tracks	67
200	160	3.760	1.400	2.500	4.480	650	Connection tracks	70
250	200	3.920	1.450	2.380	4.250	0	Connection tracks	68
250	200	3.896	1.200	2.618	4.480	900	Connection tracks	66
300	240	3.920	1.450	2.380	4.500	0	Connection tracks	71
400	320	4.000	1.500	2.450	4.800	0	Connection tracks	72

dB(A) values marked with a «*» are possible using the variant «Super Silent». Please do not hesitate to contact us for further information.